TECHNICAL APPLICATION GUIDE



ESSENTIAL SEALER'S GOLD MATT FINISH

2.5L 5L SKU: SC4U_ERS_SGM01/SC4U_ERS_SGM250/SC4U_ERS_SGM05

DESCRIPTION

SC4U ESSENTIAL SEALER'S GOLD MATT FINISH is a professional, all-purpose sealer matt look finish for all types of natural internal stone - the gold standard your stone deserves.

SC4U ESSENTIAL SEALER'S GOLD MATT FINISH is a highly effective multi-purpose indoor stone sealer. It has been developed to offer excellent sealing and oil & stain resistance to ALL types of indoor stone surfaces, including slate, limestone, granite, quartz, sandstone, travertine, marble and more. SEALER'S GOLD saves you time and money, one sealer does it all! Essential Sealer's Gold Matt Finish is a powerful impregnating sealer suitable for most internal porous textured stone and masonry surfaces. Not recommended for use on highly polished, ceramic/glazed or nonporous surfaces.

DIRECTIONS FOR USE

Before use, remove any loose debris from the work surface and ensure you have adequate personal protection, i.e gloves, suitable protective eye-wear, face mask & clothing.

- NOTE: Following the instructions below, perform a small test application on-site in an inconspicuous area prior to use. This will indicate the suitability and effectiveness of the product for your surface. If unsuitable for your requirements DO NOT PROCEED; contact us to return the product.
- 2. Before application the surface must be completely clean and dry, apply generously and evenly with a low pressure sprayer, roller, natural fibre brush or sponge, remove any excess sealer with dry cloth after 20-30 minutes.
- Apply a second application approximately 45-60 minutes repeating the process. It will take at least 24 hours before the product will offer full protection. Until this has happened, keep the surface free from water and oil spills, as stains may occur before fully cured.

Please Note: Areas not to be sealed must be protected with masking materials. It is strongly recommended when using coloured grouts that a stain test is completed before proceeding.

COVERAGE

Up to 30M² per litre.

Dependant on porosity of surface. Check the surface after application to ensure full effectiveness of impregnator.

PRECAUTIONS

KEEP OUT OF THE REACH OF CHILDREN & PETS

H302: Harmful if swallowed.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

P102: Keep out of reach of children. P262: Do not get in eyes, on skin, or on clothing.

P280: Wear protective gloves.

P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting, P302+350; IF ON SKIN; Gently wash with plenty of soap and water. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor. P332+313: If skin irritation occurs: Get medical advice.

Product SDS sheet available to download from our website.

P337+313: If eye irritation persists: Get medical advice.

Instructions on this label are a guide and should not be considered complete. In the event of failure, the manufacturer shall be obliged to replace such product proven defective. It is the user's responsibility to ascertain the suitability and safety of this product thus assuming all liability and risk thereof. For more information, refer to the Product Application Sheet available from www.stonecare4u.co.uk.

STORAGE INFORMATION

Store away from temperature extremes and direct sunlight. Use within 12 months of purchase. Once open, use within 3 months.



USAGE GUIDELINES

Drying Time	Applications/Coats	Application Method	Dilution
45-60 mins	2 coats	Brush/Sprayer/ Roller/Sponge	Undiluted